

Outdoor Security Infrared OSD Bullet Camera



AIR-491V

Model	AIR-491V
Image Sensor	1/3" Sharp Color CCD
Resolution	480 TV Lines
Effective Pixels	NTSC: 510x492 / PAL: 500x582 (H)x(V)
Min. Illumination	0.1 Lux @F1.8
Lens	2.8-12mm Vari-focal Lens
S/N Ratio	More than 52dB(AGC OFF)
Electronic Shutter	1/60(1/50)~1/100,000sec
Video Output	1.0Vp-p/75 ohm Composite
Sync. System	Internal
OSD	Built-in OSD Menu
White Balance	ATW/AWC (PUSH LOCK)/Manual
Shutter/AGC	Auto/Manual/FLK
Backlight	BLC/HLC
IR LED	36pcs
IR Distance	30M (100')
Weatherproof	IP 66
Power Source	DC12V +/- 10% @500mA w/IR on
Dimensions	83 (W)x 81 (H)x 262 (D) mm
Weight	550g
Operating Temp.	-10°C to +50°C (-14°F to +122°F)



- A. External adjustment for zoom and focus (2.8-12mm)
- B. Easy installation for unscrewing the base of the bracket



The jointed bracket allows full freedom of movement.

The elbow joint has interlocking teeth that prevent slippage.

Security screws lock down all adjustment points - at camera, at base, and at elbow pivot.

Easy Camera Setup

The 3-dimensional mini joystick on video/camera cable gives the user quick access to the OSD menu.



SETUP	
LENS	MANUAL
EXPOSURE	ATW1
WHITE BAL	OFF
BACKLIGHT	COLOR
DAY/NIGHT	OFF
DPC	SPECIAL
SPECIAL	RESET
RESET	EXIT
EXIT	

OSD Control

